





MOTOBATT GEL Technology


MOTOBATT GEL Technology


 MTX6S	Voltage	12V
	Capacity	6Ah
	Reference CCA (-18C)	95A
	Dimension (mm)	L:114 W:70 H:107
	Polar	[-][][][][+]
Replaced YUASA	YTZ7S YTX5L-BS	


 MTX7L	Voltage	12V
	Capacity	7Ah
	Reference CCA (-18C)	105A
	Dimension (mm)	L:113 W:70 H:129
	Polar	[-][][][][+]
Replaced YUASA	YTX7L-BS	


 MTX7A	Voltage	12V
	Capacity	7Ah
	Reference CCA (-18C)	110A
	Dimension (mm)	L:151 W:87 H:95
	Polar	[+][][][][-]
Replaced YUASA	YTX7A-BS	


 MTX7B	Voltage	12V
	Capacity	7Ah
	Reference CCA (-18C)	90A
	Dimension (mm)	L:151 W:65 H:94
	Polar	[+][][][][-]
Replaced YUASA	YT7BBS	


 MTX7D	Voltage	12V
	Capacity	7Ah
	Reference CCA (-18C)	105A
	Dimension (mm)	L:149 W:60 H:129
	Polar	[+][][][][-]
Replaced YUASA	12N7A-4A	

 MTX7DL	Voltage	12V
	Capacity	7Ah
	Reference CCA (-18C)	105A
	Dimension (mm)	L:149 W:60 H:129
	Polar	[-][][][][+]
Replaced YUASA	12N7A-3A	

 MTX7C	Voltage	12V
	Capacity	7Ah
	Reference CCA (-18C)	100A
	Dimension (mm)	L:135 W:76 H:123
	Polar	[+][][][][-]
Replaced YUASA	12N7-4A 12N7-4B YB7-A	

 MTX7CL	Voltage	12V
	Capacity	7Ah
	Reference CCA (-18C)	100A
	Dimension (mm)	L:135 W:76 H:123
	Polar	[-][][][][+]
Replaced YUASA	12N7-3B YB7L-B	

 MTX9	Voltage	12V
	Capacity	9Ah
	Reference CCA (-18C)	125A
	Dimension (mm)	L:137 W:76 H:133
	Polar	[+][][][][-]
Replaced YUASA	YB7-A YB9-B, YB9A-A 12N7-4A, 12N7-4B 12N9-4B-1	

 MTX9A	Voltage	12V
	Capacity	9Ah
	Reference CCA (-18C)	140A
	Dimension (mm)	L:151 W:97 H:105
	Polar	[+][][][][-]
Replaced YUASA	YTX9-BS	



50%
longer cycle life

100%
New ABS material
Non recycle ABS plastic

10%
More Battery discharge time
*More Battery discharge time.
Smooth Welding technology.
New and good!*

20%
Extra capacity
more powerful

*Ps. All data in the brochure are just for your reference. If the actual data differ from the expected data, the former should prevail. The company reserves the final interpretation

MOTOBATT GEL Technology

Gel battery Expert

More than 20 years production experience.

Premium battery leader

Focus on high quality products.

Faster delivery

Some models are ready in stock, order and go!

Communication accessibility

More than 15 years Professional export experience!



Smooth welding technology

Good welding ensures 100% No Short circuit, Extend battery life, 10% more Battery discharge time.



Silver Coated copper terminal

Up to 50% better conductivity than lead type.



European Gel


No acid leak, no acid mist


ABS 100% New ABS material
Non recycle ABS plastic


150% 50% longer cycle life.


Key 20% extra capacity
more powerful


Ω Lower internal resistance
assures bigger power.

	Voltage	12V
	Capacity	2.5Ah
	Reference CCA (-18C)	30A
	Dimension (mm)	L: 81 W: 77 H: 102
	Polar	
	Replaced YUASA	YB2.5L-B

	Voltage	12V
	Capacity	3Ah
	Reference CCA (-18C)	35A
	Dimension (mm)	L: 98 W: 56 H: 109
	Polar	
	Replaced YUASA	YB3L-A YB3L-B

	Voltage	12V
	Capacity	4.2Ah
	Reference CCA (-18C)	65A
	Dimension (mm)	L: 113 W: 70 H: 85
	Polar	
	Replaced YUASA	YB4L-A YB4L-B YTX4L-BS 12N4-3B, YTZ3-BS

	Voltage	12V
	Capacity	5Ah
	Reference CCA (-18C)	85A
	Dimension (mm)	L: 119.5 W: 60.5 H: 131
	Polar	
	Replaced YUASA	12N5-3B YB5L-B

	Voltage	12V
	Capacity	5Ah
	Reference CCA (-18C)	70A
	Dimension (mm)	L: 113 W: 70 H: 106
	Polar	
	Replaced YUASA	YTX5L-BS

	Voltage	12V
	Capacity	6.5Ah
	Reference CCA (-18C)	85A
	Dimension (mm)	L: 138 W: 66 H: 102
	Polar	
	Replaced YUASA	YB6.5L-B